




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G02B 27/22		A1	(11) International Publication Number: WO 99/59021
			(43) International Publication Date: 18 November 1999 (18.11.99)
(21) International Application Number: PCT/JP99/02434 (22) International Filing Date: 11 May 1999 (11.05.99) (30) Priority Data: 9810034.0 12 May 1998 (12.05.98) GB (71) Applicant (for all designated States except US): SHARP KABUSHIKI KAISHA [JP/JP]; 22-22, Nagaike-cho, Abeno-ku, Osaka-shi, Osaka 545-8522 (JP). (72) Inventors; and (75) Inventors/Applicants (for US only): MOSELEY, Richard, Robert [GB/GB]; 18 Trefoil Close, Horsham, West Sussex RH12 5FQ (GB). WOODGATE, Graham, John [GB/GB]; 9 Vicarage Road, Henley-on-Thames, Oxfordshire RG9 1HF (GB). EZRA, David [GB/GB]; 19 Monks Mead, Brightwell-Cum-Sotwell, Wallingford, Oxfordshire OX10 0RL (GB). (74) Agent: YAMAMOTO, Shusaku; Crystal Tower, 15th floor, 2-27, Shiromi 1-chome, Chuo-ku, Osaka-shi, Osaka 540-6015 (JP).		(81) Designated States: JP, KR, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: DIRECTIONAL DISPLAY



(57) Abstract

An autostereoscopic 3D display includes a spatial light modulator, for instance of the liquid crystal display type. A backlight and a mask form a plurality of light sources which are imaged by a lenticular screen at first notional viewing windows. A parallax barrier controls the visibility of pixels of the spatial light modulator to form second notional viewing windows. The display forms actual viewing windows whose lateral extent is equal to the product of the lateral extents of the first and second viewing windows and is less than each of these lateral extents.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

- 1 -

DESCRIPTION

DIRECTIONAL DISPLAY

5 TECHNICAL FIELD

The present invention relates to a directional display, for instance for use as a three dimensional (3D) display. Such displays may be used in: professional displays, for instance in office environments; 10 entertainment systems such as 3D video games; 3D television; medical imaging; virtual reality; and design visualization.

BACKGROUND ART

15 EP 0 656 555 discloses an observer tracking twin-panel display of the autostereoscopic 3D type. This display makes use of a beamcombiner to combine the outputs of two individual optical systems.

20 EP 0 726 482 and GB 2 297 876 disclose an autostereoscopic 3D display in which observer tracking is achieved by electronically changing the view information displayed by spatial light modulators. By changing the view information in response to movements

- 2 -

of an observer, the observer can be tracked laterally while ensuring that the correct views are perceived by the individual eyes of the observer.

5 EP 0 721 131 and GB 2 296 617 disclose a similar type of observer tracking autostereoscopic 3D display but with the ability to track longitudinal movements of an observer. In this case, longitudinal observer movements are tracked by changing the view information in vertical
10 slices of varying width.

For such lateral and longitudinal tracking displays, the viewing windows must be uniform and contiguous. Also, the width of the viewing windows is
15 important. In a three-view system, the window width should be two thirds of the average inter-ocular separation whereas, in a four-view system, the window width should be half the inter-ocular separation. The appropriate viewing conditions for such displays may be
20 achieved using spatial light modulators of the type disclosed in EP 0 625 861. However, such displays have various disadvantages. For instance, the image resolution is relatively low, in particular less than a third of the spatial resolution of the spatial light

- 3 -

modulator for each image. Further, high manufacturing tolerances are required in order to avoid visible artifacts at the boundaries of viewing windows. Complicated interlacing of the images is required on the
5 spatial light modulators. In order to provide a spatial light modulator of this type, a custom liquid crystal display (LCD) has to be manufactured or a conventional LCD panel, for instance of the delta type, has to be modified.

10

EP 0 947 208 and GB 2 320 156 disclose flat panel autostereoscopic 3D displays in which two parallax elements are used to improve the uniformity of viewing windows. One of the parallax elements defines the viewing
15 windows but creates non-uniformities within the windows, for instance because of diffraction. The other parallax element introduces inverse illumination non-uniformities for canceling or reducing the undesirable optical effects of the first parallax element. The second parallax
20 element does not modify the width or information content of the viewing windows and may be embodied as a gray-scale mask element. The embodiment shown in Figure 30 of GB 2 320 156 discloses a directional illumination system in which a backlight and mask form a plurality of light

- 4 -

sources which are imaged by a lenticular screen to form viewing windows.

It can be difficult for inexperienced observers
5 of autostereoscopic 3D displays to position themselves correctly with respect to the viewing windows or viewing zones. EP 0 860 728 and GB 2 321 815 disclose a flat panel autostereoscopic 3D display which incorporates a visual position indicator integrated with a parallax element.
10 This provides a relatively simple visual indication to the observer of correct and incorrect observer position with respect to the viewing zones or viewing windows.

EP 0 829 744, GB 2 317 295, EP 0 887 666 and GB
15 2 326 728 disclose parallax barriers which are suitable for use in directional displays and which permit different modes of operation to be achieved. Such a parallax barrier comprises polarization modifying strips for defining the slits of the parallax barrier separated by
20 regions which do not affect the polarization of incident light. A separate removable uniform polarizer is provided. A further uniform polarizer is required and may be provided by an input or output polarizer of a spatial light modulator, such as an LCD. With the removable

- 5 -

polarizer in place, a parallax barrier is formed to provide a 3D viewing mode. When the removable polarizer is removed from the optical path, the polarization modifying strips and the separating regions act as a uniformly transparent optical element for a 2 dimensional (2D) viewing mode.

Mashitani, "Autostereoscopic LCD image splitter displays", Optics Design number 12, pp36-41 (the Optical Society of Japan, 1997) discloses a single-panel 3D display comprising an LCD with front and rear parallax barriers. The two parallax barriers cooperate to produce viewing zones having less overlapping edge regions than is produced by a single parallax barrier arrangement. This arrangement requires non-directional illumination.

This arrangement narrowly constrains the profiles of the windows at the viewing plane so that the brightness of the displayed images is reduced and increased intensity variations are perceived as an observer moves by relatively short lateral distances with respect to the display. Also, the pitches of the parallax barriers are required to be substantially the same as the pixel pitch of the LCD. This requires high tolerance of alignment and

- 6 -

manufacture and results in increased cost.

Nose et al, "Rear-lenticular 3D-LCD without
eyeglasses", 3D Image Conference 1997, pp219-224
5 discloses a 3D display in which a horizontal parallax
system and a vertical parallax system cooperate to allow
autostereoscopic 3D viewing from a single LCD panel in
viewing zones restricted horizontally with the images
interlaced in adjacent rows of picture elements (pixels)
10 on the LCD. This arrangement simplifies the interface to
the LCD by permitting two images to be displayed as the
interlaced fields of the standard interlaced video format.
The horizontal parallax system defines both the
information content of viewing regions and, in combination
15 with the vertical parallax system, the form of the viewing
regions. Directional illumination is required and is
effectively split into two sub-systems, with light from
each sub-system passing through parts of the display to
define the information content of the viewing zones. Thus,
20 the directional illumination is effectively divided into
two spatially multiplexed systems, each of which is only
associated with some of the pixels of the LCD.

- 7 -

This arrangement also suffers from the disadvantage of requiring alignment of the optical elements substantially at the pixel pitch of the LCD. Further, a lenticular screen is required with the pitch of the lenticules being substantially equal to the LCD pixel pitch. Lenticular screens are difficult and expensive to manufacture with the tolerances required to achieve accurate alignment with LCD structures, particularly when compared with parallax barriers which may be made to high tolerances using standard photographic or lithographic techniques.

GB 2 252 175 discloses a single panel autostereoscopic 3D display using a double parallax barrier arrangement. This arrangement comprises two separate barrier sheets working together to define broad illumination regions with non-illuminated regions separating them. In this way, pseudoscopic viewing zones can be avoided. However, such an arrangement also suffers from spreading of the edges of the window profile illumination resulting in perceptible variations in image brightness as an observer moves laterally. Also, such an arrangement cannot provide a 2D viewing mode.

- 8 -

GB 2 317 710 discloses a directional display in which a lenticular screen is associated with an active mask arrangement forming a rear parallax barrier. The combination may be considered to act as a directional light source which illuminates an associated spatial light modulator. However, no parallax optic is associated with the spatial light modulator.

GB 2 272 555 discloses what is known as a "hybrid sandwich" type of stereoscopic display. The hybrid sandwich comprises a spatial light modulator having input and output parallax optics. The input parallax optic effectively images the light sources at a diffuser within the sandwich and so does not act as a directional illumination system.

EP 0 570 179 discloses a similar arrangement in which a hybrid sandwich is associated with a directional light source. However, the directional light source merely serves to alter the direction of input illumination to the hybrid sandwich.

- 9 -

DISCLOSURE OF THE INVENTION

According to the invention, there is provided a directional display including a spatial light modulator, a directional illumination system for directing light through the modulator, and a parallax optic associated with the modulator, wherein: the illumination system directs light towards a plurality of first notional viewing windows, each of which has a first lateral extent; the parallax optic cooperates with the modulator so that non-directional illumination of the modulator would result in the formation of second notional viewing windows, each of which has a second lateral extent; and the modulator, the illumination system and the parallax optic cooperate to form actual viewing windows, each of which has a lateral extent which is equal to the product of the first and second lateral extents and is less than each of the first and second lateral extents.

The term "lateral extent of a viewing window" means the lateral width for which the light intensity (for a maximally white image) is greater than $x\%$ of the peak intensity of the window, where x is less than 100. In theory, x can have any value less than 100 but, in practice, values of x which are so low as to be affected by stray

- 10 -

light, crosstalk, etc. should be avoided.

The illumination system may include at least one illumination source and an imaging system.

5

The illumination system may include a plurality of discrete light sources.

The imaging system may include a field lens.

10

The illumination system may include a backlight and a mask having a plurality of slits defining the illumination sources. Regions of the mask between the slits may be reflective towards the backlight. The imaging system may comprise a lenticular screen. Each lenticule of the lenticular screen may cooperate with a group of the slits to image the slits in a plurality of lobes in respective viewing windows.

15

The imaging system may include at least one holographic optical element. The illumination source may comprise a collimated light source.

20

The viewing windows may be laterally contiguous.

- 11 -

The viewing windows may include laterally spaced pairs of laterally contiguous viewing windows.

The parallax optic may include a parallax barrier.

5

The spatial light modulator may include a first and second spatial light modulators, the parallax optic may include first and second parallax optics cooperating with the first and second spatial light modulators, respectively, and the display may include a beamcombiner for combining output light from the first and second spatial light modulators. The illumination system may include a plurality of discrete light sources and a beam splitter for directing light from the light sources towards the first and second spatial light modulators.

15

The display may include a switchable diffuser cooperating with the spatial light modulator and switchable between a non-diffusing state to provide a directional display mode and a diffusing state to provide a non-directional display mode.

20

It is thus possible to provide a directional display in which directional illumination creates

- 12 -

illumination zones with light passing through the whole area of a directional display panel. The directional display panel defines the image information content visible in the whole or part of the illumination zones.

5 By using imaging optical elements to provide the directional illumination, improved illumination zone profiles can be achieved such that uniform illumination is provided in a central part of the illumination zone and the zone has sharp edges. The use of a parallax optic

10 such as a parallax barrier to define the information content of the zones provides low levels of crosstalk.

It is further possible to provide an electronically tracked autostereoscopic 3D display of the

15 beamcombiner type. Such an arrangement requires no moving parts and results in little or no visual flicker artifacts during observer tracking. A four-window system can be provided for enhanced tolerances during tracking, for instance compared with a three-view system as

20 disclosed in EP 0 726 482, EP 0 721 131, GB 2 297 876 and GB 2 296 617. Longitudinal tracking by means of view slicing can be provided and fast observer tracking at video input rates can be achieved. An image resolution equal to half the spatial resolution of the spatial light

- 13 -

modulator can be provided. The spatial light modulator may be embodied by standard liquid crystal displays without requiring any modification. Such an arrangement can make use of the same display interfacing as other flat panel two-view interlaced displays. In the case of a parallax barrier as the parallax optic, wide slits may be adopted so as to improve light efficiency and reduce diffraction effects. All of the elements may be fixed in position during manufacture so as to provide a rugged display. Stereoscopic and 2D modes of operation may easily be provided in some embodiments.

It is possible to eliminate pseudoscopic viewing regions, for instance for fixed observer position to two-view autostereoscopic displays. Such arrangements can have reduced crosstalk and may be electronically switchable to a 2D mode. Further, it is not necessary to provide any viewer position indication because even inexperienced observers have no substantial difficulty in correctly locating themselves with respect to the viewing regions.

- 14 -

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be further described, by way of example, with reference to the accompanying drawings, in which:

5

Figure 1 is a diagrammatic plan view of an autostereoscopic 3D display constituting a first embodiment of the invention;

10

Figure 2 is a diagrammatic plan view of a directional illumination system of the display of Figure 1;

15

Figure 3 is a diagrammatic plan view of another type of directional illumination system which may be used in the display of Figure 1;

20

Figures 4a and 4b are diagrammatic plan views of holographic-based directional illumination systems which may be used in the display of Figure 1;

Figure 5a illustrates a viewing window illumination profile produced by a directional illumination system of the type shown in Figure 2;

- 15 -

Figure 5b illustrates visibility profiles at the viewing windows of adjacent pixel sets produced by a spatial light modulator and parallax barrier;

5 Figure 5c illustrates the viewing window performance achieved by combining the profiles of Figures 5a and 5b;

10 Figure 6 is a diagrammatic plan view of the display of Figure 1 illustrating the creation of contiguous viewing windows in contiguous lobes;

15 Figure 7 is a diagram illustrating lateral observer tracking for the viewing windows shown in Figure 6;

20 Figure 8 is a diagrammatic plan view of an autostereoscopic 3D display constituting a second embodiment of the invention;

 Figure 9a is a diagrammatic plan view of an autostereoscopic 3D display constituting a third embodiment of the invention;

- 16 -

Figure 9b illustrates operation of the display of Figure 9a in a 2D or stereoscopic mode;

Figure 10a is a diagrammatic plan view of an
5 autostereoscopic 3D display constituting a fourth
embodiment of the invention;

Figure 10b illustrates operation of the display
of Figure 10a in a 2D or stereoscopic mode;
10

Figure 11 is diagrammatic plan view of an
autostereoscopic 3D display constituting a fifth
embodiment of the invention;

Figure 12 is a diagrammatic plan view of an
15 autostereoscopic 3D display of known type illustrating
the presence of pseudoscopic viewing zones;

Figure 13 is a diagrammatic plan view of an
20 autostereoscopic 3D display constituting a sixth
embodiment of the invention;

Figure 14 illustrates the optical performance of
the display of the Figure 13;

- 17 -

Figure 15 is a diagrammatic plan view of an autostereoscopic 3D display constituting a seventh embodiment of the invention;

5 Figure 16 is a diagrammatic plan view of an autostereoscopic 3D display constituting an eighth embodiment of the invention; and

10 Figure 17 illustrates operation of the display of Figure 16 in a 2D mode.

Like reference numerals refer to like parts throughout the drawings.

15 BEST MODE FOR CARRYING OUT THE INVENTION

20 The autostereoscopic 3D display shown in Figure 1 is of the beamcombiner type using compact illumination systems. The display comprises a backlight 1 disposed behind a mask set 2 in the form of an opaque layer having formed therein vertically extending parallel slits which act as individual light sources. A lenticular sheet 3 is disposed in front of the mask set 2 and comprises a plurality of vertically extending parallel cylindrically converging lens elements or lenticules. Each of the

- 18 -

lenticules is disposed above a group of two of the slits of the mask set 2 (This is not explicitly shown in Figure 1 and in subsequent figures, which are schematic in this respect.). The devices 1,2 and 3 form a compact
5 illuminator.

A spatial light modulator (SLM) 4 is disposed in front of the compact illuminator 1,2,3 and comprises, for example, a liquid crystal device (LCD) whose pixels are
10 arranged in columns. Image information is supplied to the SLM 4 in such a way that two stereoscopic views are spatially multiplexed on the SLM 4. In particular, alternate columns of the pixels display vertical strips of alternate ones of the stereoscopic views. A parallax
15 element 5 in the form of the parallax barrier is disposed in front of the SLM 4. The parallax barrier 5 comprises vertically extending slits which are parallel and evenly spaced laterally. Each slit of the parallax barrier 5 corresponds to two columns of pixels of the SLM 4.

20

The display further comprises a second backlight 11, a second mask set 12, a second lenticular sheet 13, a second SLM 14 and a second parallax element 15 of the same type and arrangement as the devices 1 to 5,

- 19 -

respectively. A beamcombiner 6 is arranged such that light from the devices 1 to 5 is transmitted whereas light from the devices 11 to 15 is reflected towards viewing windows 7. The beamcombiner 6 may, for example, comprise
5 a partially silvered mirror having chromatic properties so that the color of the transmitted light matches that of the reflected light. This may be achieved by providing an appropriate optical coating on the beamcombiner 6 and/or by adjusting the color balances or "gammas" of the
10 LCDs forming the SLMs 4 and 14. Further, the compact illuminator intensities are matched so that the illumination of the viewing windows matches.

Figure 2 illustrates the compact illuminator
15 1,2,3 together with the light paths which it produces. Each of the lenticules of the lenticular sheet 3 forms images of the two associated slits of the mask set 2 as illustrated by illumination regions or "first notional viewing windows" 8. The pitch of the lenticules of the
20 lenticular sheet 3 is slightly less than twice the pitch of the slits of the mask set 2 to provide view point compensation so that the images of the groups of two slits are coincident at the first notional viewing windows 8. The lateral width or extent of the windows 8 is

- 20 -

substantially equal to half the average inter-ocular separation and hence is approximately 32mm. The windows 8 are laterally spaced apart by the same amount.

5 The lateral width or extent of a viewing window is defined as the lateral width $w(x)$ for which the light intensity in the window is greater than $x\%$ of the peak or maximum light intensity in the window, where x is less than 100. Although x may be chosen arbitrarily, very low
10 values should be avoided because the intensity can be distorted by effects such as crosstalk between windows, scattering of light, etc.

 The compact illuminator 11,12,13 operates in the
15 same way but the light paths are bent by reflection at the beamcombiner 6. The relative positions and orientations of the compact illuminators and the beamcombiner are such that the illumination regions from the compact illuminators alternate laterally with each
20 other in a common plane to form the actual viewing windows 7. The first windows 8a and 8b from the compact illuminator 1,2,3 are shown in Figure 1 whereas the first windows formed by the compact illuminator 11,12,13 are shown at 8c and 8d.

- 21 -

Figure 3 illustrates an alternative form of illumination system comprising diffuse light sources 9 of defined spatial extent imaged by a field lens 10 of optically converging type at the first notional viewing windows 8. The field lens 10 may, for example, be a Fresnel lens and is of the cylindrically or spherically converging type.

Figure 4a illustrates another type of directional illumination system. The system comprises a holographic optical element 16 provided with input illumination 17 from an appropriate light source, such as a collimated light source. The holographic optical element 16 is of uniform type and generates the first notional viewing windows 8.

Figure 4b illustrates a similar directional illumination system but with a dual spatially multiplexed holographic optical element 16. Each sub-section of the element 16 generates one of the two windows 8.

Figure 5a illustrates the intensity profile of the first notional viewing windows generated by the illumination system such as 1,2,3 at the plane of the

- 22 -

viewing windows 7. This is the intensity profile which would be produced, for example, by the illumination system 1,2,3 of Figure 1 if the SLM 4 and the parallax barrier 5 were omitted. The directional illumination system, which images the light sources at the viewing windows 7, generates an intensity profile for each window of good central uniformity with sharp edges. However, undesirably high crosstalk levels between windows may be produced, for instance, because of light scatter or non-perfect surface quality. Although such crosstalk may be less than 5%, it is still highly visible to an observer and is an important source of viewing discomfort and eye fatigue.

Figure 5b illustrates the optical performance of the LCD 4 and the parallax barrier 5. In particular, Figure 5b illustrates second notional viewing windows 8' in the form of an intensity profile which would be produced, for example, by the SLM 4 and the parallax barrier 5 if the directional illumination system 1,2,3 were replaced by a non-directional illumination source and all the pixels of the SLM 4 were in their maximally transmissive optical state. This profile corresponds directly to the degree of visibility at the window plane of sets of pixels

- 23 -

of the SLM 4 which display the two sets of image data. Each of the sets of pixels is disposed in alternate columns of the SLM 4.

5 The parallax barrier 5, which may be disposed in front of the LCD 4 as shown (or behind the LCD 4) restricts visibility from the plane of the viewing windows 7 such that light from adjacent pixel columns are restricted to adjacent second notional viewing windows 8'. If an eye
10 of an observer is in one 32mm wide window 8', it receives light from every second pixel column whereas an eye in an adjacent window 8' receives light from the other pixel columns. The directional illuminators 1,2,3 and 11,12,13 distribute illumination whereas the parallax elements 5
15 and 15 cooperate with the SLMs 4 and 14 to restrict access to the image information. The parallax elements 5 and 15 do not shape the first notional viewing windows 8 but merely restrict which pixels of the SLMs 4,14 are visible within each notional window 8.

20

Figure 5c illustrates the actual viewing windows 7 in the form of an intensity profile produced, for example, by the directional illumination system 1,2,3, the SLM 4 and the parallax barrier 5 of Figure 1 with all of the

- 24 -

pixels of the SLM in their maximally transmissive optical state. The parallax barriers provide good crosstalk performance (if strong diffraction is avoided by choosing a suitably wide slit width) because of the very high contrast ratio and excellent surface quality. As shown in Figure 5b, such parallax elements are not capable of producing sharp-edged viewing regions. Accordingly, the combination of the directional illumination system and the parallax optic provides evenly illuminated viewing windows 7 with sharp edges and with low crosstalk.

The lateral extent $W_{1-5}(x)$ (as defined hereinbefore) of the actual viewing window 7 is given by:

$$W_{1-5}(x) = W_{1-3}(x) \cdot W_{4,5}(x)$$

where $W_{1-3}(x)$ is the lateral extent of the first notional viewing windows 8 and $W_{4,5}(x)$ is the lateral extent of the second notional viewing windows 8'. This expression is valid for all values of x less than 100 and greater than for the "base regions" of the window profiles which are contaminated, for example by the effects of crosstalk. For example, x may be greater than five. Also, for all such values of x , $W_{1-5}(x)$ is less than $W_{1-3}(x)$ and less than $W_{4,5}(x)$.

- 25 -

Figure 6 illustrates how the display of Figure 1 may generate more viewing windows. The SLM 4 is illustrated as providing pixel sets A and C whereas the SLM 14 is illustrated as providing pixel sets B and D. The viewing windows in which these pixels sets are visible are likewise indicated by A,B,C and D.

In addition to the images formed by each lenticule of the lenticular sheets 3 and 13 and the corresponding groups of sets of the mask sets 2 and 12, each lenticule forms images of the adjacent groups of slits in adjacent lobes of order +1 and -1 as illustrated in Figure 6 at 19 and 20. The windows and the view information contained therein are therefore repeated laterally on either side of the viewing windows A to D. The width and pitch of the viewing windows produced by the display are such that the viewing windows are substantially laterally contiguous within each lobe and the lobes are themselves substantially laterally contiguous. The uniform illumination therefore allows an observer to move between viewing regions and lobes with little or no undesirable visual artifacts. For instance, if the SLMs 4 and 14 were displaying the same image information in all of the viewing windows 7, it would be possible for an observer to move

- 26 -

the eyes between the viewing windows 7 without substantially noticeable flicker.

The generation of multiple lobes occurs naturally
5 in the case of directional illumination systems using mask sets and lenticular sheets shown in Figures 1 and 6. Similarly, the holographic optical elements 16 shown in Figure 4a and 4b may be arranged to generate the repeating pattern. In the case of the illumination system
10 illustrated in the Figure 3, the generation of multiple lobes may be achieved by repeating the pattern of light sources 9 with uniform lateral pitch.

In order to increase the viewing freedom so that
15 an observer can perceive a 3D image throughout an extended viewing region, electronic observer tracking may be provided as disclosed in EP 0 726 482, GB 2 297 876, EP 0 721 131 and GB 2 296 617. Figure 7 illustrates how lateral tracking of observer position may be performed.
20 The viewing windows in two lobes are illustrated at A to D with the relative lateral positions of the eyes of an observer being shown for four observer positions. The pixel set which is visible in each viewing window is also indicated by the same letter, so that the pixel set A is

- 27 -

visible in the viewing window A and so on.

In the first observer position, the left eye of the observer is in the viewing window D and the right eye
5 of the observer is in the viewing window B of one of the lobes. Left image information is displayed by the pixel sets C and D whereas right image information is displayed by the pixel sets A and B. In the next position, the left
10 eye has just moved into the viewing window C whereas the right eye has just moved into the viewing window A. It is therefore not necessary to change the image information displayed by the pixel sets.

In the next observer position, the left eye is in
15 the middle of the viewing window C and the right eye is in the middle of the viewing window A. The image data are changed such that left image information is displayed by the pixel sets B and C whereas right image information is displayed by the pixel sets A and D. The final
20 illustrated observer position is such that the left eye is at the boundary between the viewing windows B and C of the first lobe whereas the right eye is at the boundary between the viewing window A of the first lobe and the viewing window D of the second lobe. The left and right

- 28 -

eyes of the observer therefore continue to see the left and right views, respectively, as the observer moves further to the right without having to change the image data displayed by the pixel sets.

5

The resolution of the image seen by each eye of the observer is half the spatial resolution of each of the SLMs 4 and 14. The perceived resolution is therefore twice that which would be seen on a display using a single
10 SLM. Further, viewing freedom tracking tolerances are improved with respect to a three window tracking system. In such a system, the closest an eye would theoretically approach a window boundary under normal operation is 11mm whereas, for the four window system illustrated in Figure
15 8, this is increased to 16mm. Accordingly, the tracking system accuracy and speed may be relaxed and/or improved performance may be achieved with existing components and controls.

20

Figure 8 illustrates a beamcombiner display of a type similar to that illustrated in Figure 1 but using a single set of light sources 9 to illuminate both SLMs 4 and 14. Light from the light sources 9 is directed towards a beamsplitter 21 which reflects approximately

- 29 -

half of the light and transmits the remainder. The reflected light is reflected by a mirror 22 to a field lens in the form a large format Fresnel lens 10a, which images the light through the SLM 4, the parallax barrier 5 and the beamcombiner 6 at the viewing windows 7. Light transmitted by the beamsplitter 21 is reflected by a mirror 23 to a similar Fresnel lens 10b, which images the light through the SLM 14, the parallax barrier 5 and by reflection from the beamcombiner 6 at the viewing windows 7.

The light sources 9 are shown as comprising switchable lamps. As described hereinbefore, in order to provide a plurality of lobes, the light sources 9 have to be repeated and the lamps shown in Figure 8 are switchable so that lamps which are not currently required during observer tracking operation may be switched off.

Figure 9a shows a display of type shown in Figure 1 but in which the parallax barriers 5 and 15 are replaced by parallax barriers of the type disclosed in EP 0 829 744, GB 2 317 295, EP 0 887 666 and GB 2 326 728. The parallax barrier for the SLM 4 comprises a polarization barrier 25 and a removable polarizer 26. The polarization

- 30 -

barrier 25 comprises slit regions which rotate the polarization of light from the SLM 4 by 90° separated by barrier regions which do not alter the polarization. For instance, the SLM 4 may comprise an LCD having a linear output polarizer so that light incident on the polarization barrier 25 has a defined linear polarization. The removable polarizer 26 has a polarizing direction such that light from the slit regions of the barrier 25 is transmitted whereas light from the barrier regions is extinguished. Alternatively, the polarizers 26 and 28 can be combined into a single polarizer positioned at the output of the display, positioned after the beamcombiner 6.

Similarly, the parallax barrier associated with the SLM 14 comprises a polarization barrier 27 and a removable polarizer 26 of the same type as the barrier 25 and the polarizer 26, respectively.

The display further comprises a switchable diffuser 29 disposed between the lenticular sheet 3 and the SLM 4 and a switchable diffuser 30 disposed between the lenticular sheet 13 and the SLM 14. The diffusers 29 and 30 may, for example, comprise diffuser sheets which

- 31 -

may be physically inserted into and removed from the optical paths through the display. Alternatively, the diffusers may be electronically controlled so as to be switchable between low and high diffusion states. An
5 example of such a device is a polymer dispersed liquid crystal (PDLC).

Figure 9a illustrates operation of the display in the autostereoscopic 3D mode. The diffusers 29 and 30 are
10 in the low diffusion or clear state and the polarizers 26 and 27 are in place. Thus, the diffusers 29 and 30 have no substantial effect on operation of the display whereas the polarization barriers 25 and 27 and the removable polarizers 26 and 28 act as parallax barriers
15 in front of the SLMs 4 and 14. Operation of the display is therefore as described hereinbefore.

Figure 9b illustrates operation of the display in a stereoscopic 3D mode or in a high resolution 2D mode.
20 The removable polarizers 26 and 28 have been removed and the diffusers 29 and 30 have been switched to the diffusing state.

- 32 -

Removal of the polarizers 26 and 28 disables the parallax barriers whereas operation of the diffusers 29 and 30 in the diffusing state causes the illumination system to become non-directional. Thus, all of the pixels of both SLMs 4 and 14 are visible throughout and extended viewing region as indicated at 30. When viewed without viewing aids, both eyes of the observer see the whole of the SLMs 4 and 14, so that a 2D image of twice the spatial resolution of each of the SLMs 4 and 14 may be displayed. Alternatively, if output polarizers of the SLMs 4 and 14 are arranged so as to provide orthogonal polarizations, the display may be used stereoscopically through suitable polarizing glasses throughout a wide viewing region.

Whereas the display illustrated in Figures 9a and 9b is of the front parallax barrier type, the display illustrated in Figures 10a and 10b is of the rear parallax barrier type. Thus, the polarization barrier 25 is disposed between the SLM 4 and the switchable diffuser 29 whereas the polarization barrier 27 is disposed between the SLM 14 and the switchable diffuser 30. The polarizer 26 is fixed and is disposed between the back light 1 and the mask set 2 whereas the polarizer 28 is fixed or permanently in the optical path and is disposed between

- 33 -

the back light 11 and the mask set 12.

Figure 10a illustrates the autostereoscopic 3D mode of operation, in which the diffusers 29 and 30 are in the clear state. Operation is substantially described hereinbefore.

Figure 10b illustrates operation in the stereoscopic 3D mode or in the 2D mode. The switchable diffusers 29 and 30 are in the diffusing state. This has two effects. First of all, the directionality of the compact illuminators is destroyed. Secondly, polarized light from the polarizers 26 and 27 is depolarized so that the polarization barriers 25 and 27 cease to act as parallax barriers. Thus, operation in this mode is substantially the same as the operation described hereinbefore with reference to Figure 9b.

The display shown in Figure 11 differs from that shown in Figure 1 in that the compact illuminators are replaced by holographic optical elements 16a and 16b together with collimated light sources 1a and 1b to provide directional illuminators of the type illustrated in Figure 4a or 4b. An advantage of holographic optical elements

- 34 -

over conventional optics is that the off-axis viewing zones may be produced without increased aberrations associated with off-axis imaging from conventional optical systems. Although the light sources 1a and 1b are shown as being collimated, other types of sources may be used so that the rear illumination of the elements 16a, 16b corresponds to the recording wave-fronts of the holograms.

Figure 12 illustrates a known type of single panel autostereoscopic 3D display of the front parallax barrier type. The viewing windows generated by this display are shown at 7 with L indicating windows where left eye views are visible and R indicating windows where right eye views are visible. Provided the left and right eyes of an observer are disposed in left and right viewing windows, respectively, as shown for observer A, the observer will correctly perceive the 3D image being displayed (orthoscopic viewing). However, an observer may be positioned with the left eye in a right window and the right eye in a left window as illustrated for observer B. This is termed pseudoscopic viewing and gives a confusing impression which is uncomfortable and may lead to false depth information. It can be difficult for

- 35 -

untrained observers to distinguish between orthoscopic and pseudoscopic viewing.

Figure 13 illustrates a single panel
5 autostereoscopic 3D display having a compact illuminator
1,2,3 of the type illustrated in Figure 1 for forming three
pairs of discrete spaced viewing windows 7a,7b and 7c.
The display further comprises a single SLM 4 and a single
parallax barrier 5 of the type illustrated in Figure 1
10 for providing a two- view display. The rear surface of
the mask 2 is made reflective to permit light to be recycled
so as to improve the illumination efficiency of the
display.

15 The display is illustrated in Figure 13 as
producing the viewing windows 7a, 7b and 7c such that there
is a non-illuminated gap substantially equal to the
average inter-ocular spacing between adjacent viewing
windows. It is therefore impossible for an observer to
20 be in a pseudoscopic viewing position in the plane of the
viewing windows so that pseudoscopic viewing is
impossible.

- 36 -

Figure 14 illustrates at 32 the pattern of windows produced by the combination of the SLM 4 and the parallax barrier 5. The illumination profile produced by the compact illuminator is illustrated at 33 and the resultant information distribution is illustrated at 34. Because alternate pairs of viewing windows are suppressed, pseudoscopic viewing is prevented so that the display is easier to use by an untrained observer. Further, the display exhibits lower crosstalk than for conventional displays of the type illustrated in Figure 12. In particular, light which would otherwise spread from adjacent windows on both sides of a window of interest, thus causing crosstalk, is reduced because each effective viewing window has only one adjacent illuminated window, the window on the other side being suppressed by the lack of illumination. Light can only spread from one side so that the amount of crosstalk is substantially halved. Undesirable visual artifacts resulting from crosstalk are therefore substantially reduced.

20

Any of the previously described directional illumination systems may be used and Figure 15 illustrates a display of the type shown in Figure 13 with the compact illuminator replaced by a holographic illumination system

- 37 -

of the type illustrated in Figure 11 and comprising a collimated light source 1 and a holographic optical element 16.

5 Figure 16 illustrates the display of the type shown in Figure 13 but of the rear parallax barrier type in which the parallax barrier is formed by a polarization barrier 25 of the same type as described with reference to Figure 9a to 10b. The polarization barrier 25 cooperates with
10 an input polarizer of the SLM 4 to act as a parallax barrier when receiving polarized light from the compact illuminator 1, 2, 3. The compact illuminator differs from that shown in Figure 10a in that the polarizer is combined with the mask 2 such that the mask comprises strips of
15 polarizer sheet separated by opaque strips. With the switchable diffuser element 29 in the non-diffusing mode, the display operates in the 3D autostereoscopic mode as described hereinbefore with reference to Figure 13.

20 Figure 17 illustrates the display of Figure 16 operating in a 2D mode. The diffuser 29 is switched to the diffusing mode so as to destroy the polarization produced by the polarized mask 2 and so as to destroy the directionality of the illuminator 1,2,3. The parallax

- 38 -

barrier is thus rendered ineffective and the illuminator 1,2,3 act as a near-Lambertian light source to allow a full resolution 2D image to be viewed over a wide range of angles.

5

INDUSTRIAL APPLICABILITY

According to the present invention as set forth above, it is thus possible to provide a directional display in which directional illumination creates illumination zones with light passing through the whole area of a directional display panel. The directional display panel defines the image information content visible in the whole or part of the illumination zones. By using imaging optical elements to provide the directional illumination, improved illumination zone profiles can be achieved such that uniform illumination is provided in a central part of the illumination zone and the zone has sharp edges. The use of a parallax optic such as a parallax barrier to define the information content of the zones provides low levels of crosstalk.

It is further possible to provide an electronically tracked autostereoscopic 3D display of the beamcombiner type. Such an arrangement requires no

- 39 -

moving parts and results in little or no visual flicker artifacts during observer tracking. A four-window system can be provided for enhanced tolerances during tracking. Longitudinal tracking by means of view slicing can be provided and fast observer tracking at video input rates can be achieved. An image resolution equal to half the spatial resolution of the spatial light modulator can be provided. The spatial light modulator may be embodied by standard liquid crystal displays without requiring any modification. Such an arrangement can make use of the same display interfacing as other flat panel two-view interlaced displays. In the case of a parallax barrier as the parallax optic, wide slits may be adopted so as to improve light efficiency and reduce diffraction effects. All of the elements may be fixed in position during manufacture so as to provide a rugged display. Stereoscopic and 2D modes of operation may easily be provided in some embodiments.

It is possible to eliminate pseudoscopic viewing regions, for instance for fixed observer position to two-view autostereoscopic displays. Such arrangements can have reduced crosstalk and may be electronically switchable to a 2D mode.

- 40 -

Further, it is not necessary to provide any viewer position indication because even inexperienced observers have no substantial difficulty in correctly locating themselves with respect to the viewing regions.

- 41 -

CLAIMS

1. A directional display comprising:

a spatial light modulator;

5 a directional illumination system for directing light through the modulator; and

a parallax optic associated with the modulator,

wherein:

10 the illumination system directs light towards a plurality of first notional viewing windows, each of which has a first lateral extent;

the parallax optic cooperates with the modulator so that non-directional illumination of the modulator would result in the formation of second notional viewing
15 windows, each of which has a second lateral extent; and

the modulator, the illumination system and the parallax optic cooperate to form actual viewing windows, each of which has a lateral extent which is equal to the product of the first and second lateral extents and is
20 less than each of the first and second lateral extents.

2. A display according to claim 1, wherein the illumination system comprises at least one illumination source and an imaging system.

- 42 -

3. A display according to claim 2, wherein the illumination system comprises a plurality of discrete light sources.
- 5 4. A display according to claim 3, wherein the imaging system comprises a field lens.
5. A display according to claim 2, wherein the illumination system comprises a backlight and a mask
10 having a plurality of slits defining the illumination sources.
6. A display according to claim 5, wherein regions of the mask between the slits are reflective towards the
15 backlight.
7. A display according to claim 5, wherein the imaging system comprises a lenticular screen.
- 20 8. A display according to claim 7, wherein each lenticule of the lenticular screen cooperates with a group of slits to image the slits in a plurality of lobes in respective viewing windows.

- 43 -

9. A display according to claim 2, wherein the imaging system comprises at least one holographic optical element.

5 10. A display according to claim 9, wherein the illumination source comprises a collimated light source.

11. A display according to claim 2, wherein the viewing windows are laterally contiguous.

10

12. A display according to claim 2, wherein the viewing windows comprise laterally spaced pairs of laterally contiguous viewing windows.

15 13. A display according to claim 1, wherein the parallax optic comprises a parallax barrier.

14. A display according to claim 1, wherein the spatial light modulator comprises first and second spatial light modulators, the parallax optic comprises first and second parallax optics cooperating with the first and second spatial light modulators, respectively, and the display comprises a beamcombiner for combining output light from the first and second spatial light modulators.

20

- 44 -

15. A display according to claim 14, wherein the illumination systems comprises a plurality of discrete light sources and a beamsplitter for directing light from
5 the light sources towards the first and second spatial light modulators.

16. A display according to claim 1, further comprising a switchable diffuser cooperating with the spatial light
10 modulator and switchable between a non-diffusing state to provide a directional display mode and a diffusing state to provide a non-directional display mode.

FIG 1




FIG 3







FIG 2







SUBSTITUTE SHEET (RULE 26)

2 / 11

FIG 4 aFIG 4 b

SUBSTITUTE SHEET (RULE 26)

3 / 11

FIG 5 aFIG 5 bFIG 5 cFIG 6

SUBSTITUTE SHEET (RULE 26)

4 / 11

FIG 7







FIG 8



5 / 11

FIG 9 aFIG 10 a

SUBSTITUTE SHEET (RULE 26)

6 / 11

FIG 9 b






FIG 10 b





SUBSTITUTE SHEET (RULE 26)

7/11

FIG 11

8/11

FIG 13FIG 12

SUBSTITUTE SHEET (RULE 26)

FIG 14




FIG 15






FIG 16



11/11

FIG 17

SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/JP 99/02434

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G02B27/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 G02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 764 869 A (SHARP KK) 26 March 1997 (1997-03-26) column 4, line 18 -column 5, line 17; figure 1	1
A	EP 0 729 054 A (LUEDER ERNST) 28 August 1996 (1996-08-28) column 4, line 28 -column 6, line 43; figures 2,5,7	1
A	EP 0 833 183 A (SHARP KK) 1 April 1998 (1998-04-01) cited in the application column 16, line 37 - line 50; figure 38	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance
"E" earlier document but published on or after the international filing date
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
"O" document referring to an oral disclosure, use, exhibition or other means
"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
"&" document member of the same patent family

Date of the actual completion of the international search

15 September 1999

Date of mailing of the international search report

22/09/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Hervé, D

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

P 99/02434

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0764869 A	26-03-1997	GB 2273577 A	22-06-1994
		GB 2284487 A	07-06-1995
		DE 69323846 D	15-04-1999
		DE 69323846 T	26-08-1999
		EP 0602934 A	22-06-1994
		JP 6258597 A	16-09-1994
		US 5726800 A	10-03-1998
		EP 0656555 A	07-06-1995
		JP 7218865 A	18-08-1995
EP 0729054 A	28-08-1996	DE 19506648 A	29-08-1996
		US 5777787 A	07-07-1998
EP 0833183 A	01-04-1998	GB 2317710 A	01-04-1998
		JP 10142572 A	29-05-1998

Form PCT/SA/210 (patent family annex) (July 1992)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.